

# FIXATOR

## PRODUCT DESCRIPTION

ISOWEIR FIXATOR is a structurally flexible modified acrylic copolymer based primer material that enables the application of products such as water-based insulation and flexible paint on a solid substructure, especially for exterior applications.

## AREAS OF USE

Cement based plastered surfaces, Water based old painted surfaces, Concrete and brick surfaces.

## APPLICATION

**Surface Preparation:** Free particles on the surface should be removed by mechanical means and the surface should be clean and dry. Surface defects should be filled with putty in such a way that optical unity is achieved.

**Product Preparation and Application:** The product is ready to use, no thinning is required. ISOWEIR FIXATOR is applied in one coat without thinning, taking into account the ambient conditions. It is recommended to moisturize the floor at high floor temperatures.

**Points to be Considered:** Eyes should be protected during the application. It is recommended to wear gloves. In case of skin contact, wash thoroughly with plenty of water and soap. In case of contact with eyes, consult a doctor.



## FEATURES, ADVANTAGES

- ◆ It eliminates sanding and chalking on weak floors.
- ◆ It reinforces the texture of any mineral-based, porous substrate.
- ◆ It prevents blistering and flaking by ensuring full compatibility with flexible paint and insulation layers applied on top.
- ◆ It eliminates surface absorbency that is different on repaired surfaces. The paint prevents color inconsistencies.
- ◆ When applied alone, it reduces surface water absorbency without disrupting vapor balance.

## TECHNICAL SPECIFICATIONS

Color	White Liquid
Appearance	Translucent
Density (20 °C)	1,00 – 1,10 gr/cm <sup>3</sup> (TS EN ISO 2811)
Solid Matter (% Weight)	%20 (ASTM D 4209)
PH (25 °C)	8-9 (ASTM E70)
Application Temperature (°C)	+5 °C – 35 °C
Application Apparatus	Brush, roller
Thinning Rate	None
Mixture Life (20 °C)	-
Amount of Use m <sup>2</sup> /kg	0,150 – 0,200 kg (double coat)
Drying Time (20 °C)	Surface drying 30 minutes, Paint and insulation application 3 hours, Full Curing 24 hours
Packaging	20 kg – 10 kg – 5 kg Plastic drums
Storage Temperature	It should be stored in a place not exposed to direct sunlight, protected from frost, in closed packaging at 5 °C - 35 °C.
Storage Duration	1 Year
Quality Certificate	ISO 9001

## HEALTH AND SAFETY INFORMATION

- ◆ Please consider the hazard and precautionary statements indicated on the product packaging.
- ◆ Follow the guidelines specified in the product's safety data sheet.
- ◆ In case of unexpected health issues, consult the nearest healthcare facility.

