

SB. M VİBAR

PRODUCT DESCRIPTION

It is a water-based special coating applied to metal surfaces with high adhesion strength obtained from emulsion of synthetic based resins, waxes and anti-corrosion additives.

APPLICATION

Product Preparation and Application: The product is ready to use in its packaging. It should be mixed well before use. It is applied by special production single coat pulverized or plastering method. It provides high coverage.

HEALTH AND SAFETY INFORMATION

- ◆ Please consider the hazard and precautionary statements indicated on the product packaging.
- ◆ Follow the guidelines specified in the product's safety data sheet.
- ◆ In case of unexpected health issues, consult the nearest healthcare facility.





TECHNICAL SPECIFICATIONS

Color	Black
Gloss	Semi-matte - Matte
Appearance	-
Density (20 °C)	1,40 – 1,60 gr/cm ³
Dry Film Thickness	-
Solid Matter (% Weight)	%63 - %78
Viscosity (25 °C)	100.000 – 130.000 cPs
PH (25 °C)	8,2 – 8,5
Elongation at Break	-
Water Transmission Rate	-
Heat Strength (°C)	-
Application Temperature (°C)	5 °C – 35 °C
Application Apparatus	Special line tools, airless systems, pneumatic systems, roller, brush
Thinning Rate	-
Amount of Use m ² /kg (70 – 80 microns)	0,200 kg (single coat)
Drying Time (20 °C)	In open air: 15 minutes In drying oven (30 - 35°C) : In wind tunnel: 4 - 5 minutes Full Curing: 24 hours
Packaging	20 kg Plastic bucket
Storage Temperature	It should be stored in a place not exposed to direct sunlight, protected from frost, in closed packaging at 5 °C - 35 °C.
Storage Duration	1 Year
Quality Certificate	ISO 9001

